














CHOOSING THE RIGHT SECURITY HANDLE

Great Lakes SEAL														
														
	GL-Seal-R1000	GL-Seal-R3000	GL-Seal-R3000KP	GL-Seal-R5000	GL-Seal-R5000KP	GL-Seal-E1102	GL-Seal-50	GL-Seal-20	GL-Seal-65	GL-Seal-67	GL-Seal-BL	GL-Seal-EL	GL-Seal-CL	
Authentication Method	Depends on customer's software	Transponder card	Transponder Card + PIN	Transponder Card	Transponder Card + PIN	Depends on customer's software	PIN	Transponder Card	Transponder Card	Transponder Card	Biometrics	Depends on customer's software	Transponder Card	
Access Control Software	3rd Party Software Required	Manufacturer Administration Suite	Manufacturer Administration Suite	Manufacturer Administration Suite	Manufacturer Administration Suite	3rd Party Software Required	No	No	3rd Party Software Required	3rd Party Software Required	DAS-SQL Software	DAS-SQL Software	DAS-SQL Software	
Cut Out Size	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	Custom Cutout Required	20 x 150mm (spacer required)	20 x 150mm (spacer required)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	20 x 150mm (GLCC standard)	
Price	\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$\$	\$\$\$	\$	\$	\$\$	\$\$	\$\$\$	\$\$	\$\$\$	
Typical Lead Time*	1-2 days	1-2 days	1-2 days	1-2 days	1-2 days	1-2 days	4-10 weeks	4-10 weeks	4-10 weeks	4-10 weeks	1-2 days	1-2 days	1-2 days	
Other Key Features	-Easily integrates into an existing facility management system	-Well suited for many enclosures located in same location	-Well suited for many enclosures located in same location -Dual factor authentication	-Well suited for enclosures located in different rooms	-Well suited for enclosures located in different rooms -Dual factor authentication	-IP65 rated -Black or white color -Outdoor Applications	-Battery Powered (3 AA) -Up to 20 unique user codes -Manager key w/ 9V electrical override	-Battery Powered (3 AA) -Accepts MIFARE, DESFire and HID smart cards -Manager key w/ 9V electrical override	-Accepts HID iCLASS, MIFARE Classic, MIFARE Plus, MIFARE DES-Fire, HID 125 kHz, EM 125kHz -Wiegand Output -Key override	-Accepts MIFARE Classic, MIFARE Plus, MIFARE DES-Fire -Wiegand Output -Key override	-Fingerprint access -Option for EMKA (GER) handle or Southco (USA) Handle -Key override	-Standard electronic lock -Option for EMKA (GER) handle or Southco (USA) Handle -Key override	-Accepts Prox or Mifare -Option for EMKA (GER) handle or Southco (USA) Handle -Key override	
Notes	flat fee for the Administration Suite Software											DAS-SQL Software pricing based on number of units		

Key Questions for Product Selection

1. What enclosure are you looking to secure?
2. How many enclosures are you looking to secure?
3. Are the enclosures located in different rooms, floors or buildings?
4. Are you interested in biometric authentication, card authentication, PIN authentication, or a combination?
5. Do you want to integrate into an existing management system/software platform?
6. If interested in card authentication - What types of cards are required? High-Frequency 13.56 MHz (iClass, Mifare, DESFire) cards, or Low-Frequency 125 kHz (Prox) cards, or other?

Additional Notes

There are additional handles available depending on customer needs.

Many accessories are required for operation of the handles (i.e., access control units, wiring harnesses, door contacts, power supply, etc.)

Please contact GLCC Tech Support for additional information at TechSupport@greatcabinets.com

*Lead time dependent on vendor stock levels. Typical lead time does not include shipping transit time. Call GLCC Tech Support for official lead time